

36"/48"/54"

# **TrimStar**

With the Trimstar hydro, we definitely walk the walk.

## FEATURES

- Kawasaki FS Premium Commercial Duty Engines
  - 3yr warranty
- 36", 48" or 54" side discharge decks
- Patented H-Bar™ steering system
  - Comfortable, User Friendly!
- Wide stance for increased stability
- 3.4-gallon fuel tank
- No daily lube points
- Superior drive system - integrated, serviceable ZT2800 transmissions
- Floating decks adjustable from operator's position

**2** YEAR | **NO** HOUR LIMIT  
**LIMITED WARRANTY**

\* See your local Hustler dealer for complete warranty details.

**LIMITED LIFETIME WARRANTY**  
LEADING EDGE OF DECK

\* Original Purchaser Only

[www.hustlerturf.com](http://www.hustlerturf.com)

PN 601990 1-13



**HUSTLER**  
Cutting Grass Not Corners



# TrimStar

## 36"/48"/54"

### Engines

Kawasaki FS481	Kawasaki FS541	Kawasaki FS600	Kawasaki FS691(Electric Start)
14.5hp	15hp	18.5hp	23hp

More Engine Information: • [www.kawpowr.com](http://www.kawpowr.com)

**Starting:** Recoil (electric start on FS691)

**Ignition:** Electronic

**Charging System:** 12-volt (see engine manufacturer specs)

**Fuel:** Unleaded gasoline - maximum of 10% ethanol in fuel (see engine manufacturer specs)

**Fuel Filter:** Replaceable, automotive-type

**Air Cleaner:** Dual element

**Cooling:** Air cooled. Fly-wheel fan

**Governor:** Mechanical

#### TRACTION DRIVE SYSTEM

**Type:** Dual hydrostatic. Hydro-Gear ZT 2800

**Pump Drive:** V-belt drive from engine crankshaft

**Ground Speed:**

Forward: Infinitely variable 0-6.3 mph (0-10.1 kph)  
Reverse: 0-2 mph (0-3.2 kph)

**Steering:** Patented, self-centering H-Bar™ Steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with the easy to learn, easy to operate H-Bar Steering.

**Turning Radius:** True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

**Brakes:**

Service: Hydrostatic dynamic braking

Parking: Internal transmission mechanical brake.

**Tires:**

Front: Two - 11 x 4 - 4, smooth, semi-pneumatic  
Drive: 36 in: 18 x 6.50 - 8, turf tread  
48 in: 20 x 10 - 10, turf tread  
54 in: 20 x 10 - 10, turf tread

**Capacities**

Fuel System: 3.4 US gal (12.9 l)

#### GENERAL INFORMATION

**Safety Features:** Operator presence safety-interlock system. Side discharge deck with discharge chute

**Construction:** Mainframe is 1.50 x 2.00 x .120 wall steel tubing.

**Controls:** Hand-operated throttle/choke, ignition switch, mower clutch switch

**Indicators:** Hour meter, oil pressure warning light (electric start model only)

#### DIMENSIONS

**Height:** 40.9 in (103.8 cm)

**W/36 in Deck:**

Length: 75 in (190.5 cm)

Overall Width: 38 in (96.5 cm) w/dischute up

Tire-to-tire Width: 35 in (88.9 cm)

Weight: 581 lbs (263.5 kg)

**W/48 in Deck:**

Length: 75 in (190.5 cm)

Overall Width: 50.4 in (128.02 cm) w/dischute up

Tire-to-tire Width: 46.75 in (118.7 cm)

Weight: 660 lbs (299 kg)

**W/54 in Deck:**

Length: 76.12 in (193.34 cm)

Overall width: 56.5 in (143.5 cm) w/dischute up

Tire to Tire: 46.75 in (118.74 cm)

Weight: 685 lbs (310 kg)

#### DECKS

**Side Discharge:** 36", 48" or 54"

**Type:** 36" fixed, side-discharge using two blades. No anti-scalp wheels. 36" decks are suspended by solid links in three places. 48" and 54" free-floating, side-discharge using three blades. Deck-mounted anti-scalp wheels to improve flotation in rolling and uneven terrain. 48/54" decks are suspended by chains in four corners.

**Construction:** 36 in Deck: 7-gauge deck plate with 11-gauge doublers. 48/54 in Deck: 11-gauge deck plate with 11-gauge doublers. 1" x 3/8" steel bar reinforced impact areas on front and trim edges, heavily-reinforced front edge. Lifetime warranty on leading edge of deck. Deck housing is 4 in deep to provide room for high-capacity mowing discharge side

**Cutting Heights:** Hand operated deck-lift in .25 in increments from 1.5 in to 4.5 in (.1 cm increments, 3.18 cm to 11.43 cm)

**Main Blades:** Heavy-duty, heat-treated, 10B38 steel blades

**36 in Deck:** 20.5 in x 2.50 in x .204 in RH blade  
13.75 in x 2.50 in x .204 in LH blade

**48 in Deck:** 16.5 in x 2.50 in x .204 in

**54 in Deck:** 18.5 in x 2.50 in x .204 in

**Mowing Blades:** Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.

**Blade Tip Speed:** 36 in: 18,400 fpm  
48 in: 18,600 fpm  
54 in: 18,920 fpm

**Deck Drive:** V-belt drive from engine with electric clutch to spindles. Spring tension idler pulleys

**Discharge Chute:** High density, rubberized

**Trim Capacity (left side):**

36 in: 0 in (0 cm)

48 in: 1.2 in (5.08 cm)

54 in: 5 in (12.7 cm)

#### ACCESSORIES

**Mulch Kits:** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

**Deck-Mounted Catcher:** Easily-installed, side-mounted catcher holds 3.5 bushels.

Compatible with after-market skulkies and trailers

*Specifications subject to change without notice.*

