

42"

ZEON

Just unplug and mow!

FEATURES

- World's first electric zero-turning radius riding mower!
- Able to mow over 1 acre on a single charge!
- Green friendly - zero emissions
- Nearly zero maintenance
- Clean and neat - no belts, filters, fluids, etc.
- No engine noise - much quieter than gasoline-powered equipment!
- SmoothTrak™ Steering w/ patented automatic park brake system
- Heavy Duty welded steel deck and tubular frame.
- 42" side-discharge/mulching deck
- 18" drive tires, 11" caster tires
- Standard, Certified ROPS and seat belt

WARRANTY

3 YEAR LIMITED

RESIDENTIAL

OR

WARRANTY

1 YEAR LIMITED

COMMERCIAL

* See your local Hustler dealer for complete warranty details.

www.hustlerturf.com



HUSTLER 
Cutting Grass Not Corners

ZEON

48-volt/42-inch side-discharge deck

42"

Charge Time 16 hours (standard charger)

TRACTION DRIVE SYSTEM

Ground Speed

Forward: 0-6 mph (0-9.65 kph) infinitely variable
Reverse: 0-3 mph (0-4.8 kph) infinitely variable

Steering Twin-lever, SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-radius turns are all controlled with hand-operated controls

Turning Radius True zero radius. Turns within its own length. Counter-rotating, independent drive wheels

Brakes

Service: Dynamic braking
Parking: Internal Cog

Tires Front: Two – 11 x 4 – 5, smooth, pneumatic
Drive: 18 x 8.50 – 8, turf tread

GENERAL INFORMATION

Safety Features Operator presence safety-interlock system. Side discharge deck with discharge chute

Seat Molded-vinyl seat. Fore and aft adjustment. Seat-pan suspension springs standard.

Construction Mainframe is 1.50 x 2.00 x .120 wall steel tubing.

Controls Hand-operated ignition switch

Indicators Digital Display: Hours, charge level, vehicle status, trouble codes

DIMENSIONS

Height 44.5 in (113.3 cm)
72 in (182.82 cm) w/ ROPS

W/42 in Deck

Length: 69 in (175.2 cm)
Overall Width: 44 in (111.76 cm) w/discharge chute up
Tire-to-tire Width: 41 in (104.14 cm)
Tire-to-tire Width: 45 in (114.3 cm) front to back
Weight: 783 lbs (355.16 kg)
Weight: 814 lbs (369.22 kg) w/ROPS

DECKS

Side-Discharge Decks 42"

Type Free-floating deck using two blades. Deck is suspended at the corners. Includes deck-mounted rollers to improve flotation in rolling and uneven terrain.

Construction 11 ga, .120 in (.30 cm) welded steel with 11 ga, .120 in (.30 cm) doubler welded onto motor mount areas. Solid 1 in x .25 in (2.54 cm x .635 cm) steel bars reinforce impact areas on trim edges. Steel deck housing is 4 in (10.16 cm) deep which allows high-capacity mowing.

Cutting Heights Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.18 cm to 11.43 cm).

Mowing Blades Heavy-duty, heat-treated, low-lift steel
42 in: 2-20.5 in x 2.5 in x .20 in

Blade Tip Speed 42 in: 15,200 fpm

Deck Drive Each blade direct driven by electric motor.

Discharge Chute High density, rubberized.

Width of Cut 42 in: 40.4 in (103 cm)

Trim Capacity (left side) 42 in: 2.25 in (5.75 cm)

ACCESSORIES

Mulch Kit Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.

Light Kit

2-Bag Catcher 5.0 bushel

High-Performance Charger Charge your batteries in 5.5 hours

Steering Extension Kit

Specifications subject to change without notice.

